



J&K STATE POLLUTION CONTROL BOARD

Jammu /Srinagar (www.jkspcb.nic.in)

CONSENT ORDER

SPCB 824 of 2016 dated 03-12-2016

Consent to **Operate (Renewal)** under section 25/26 of the Water (Prevention & Control of Pollution) Act, 1974, and under section 21 of the Air (Prevention & Control of Pollution) Act, 1981, as amended is granted in favour of

Sh. Pankaj Aggarwal (Partner)

M/s Vijay Steel Industries

Ph II, SIDCO Industrial Complex Bari Brahamana

for a period upto **May 2019** for a category of **Red** as per revised classification of industrial sector, subject to the following terms and conditions in a time bound manner:

1. The consent granted by the Board is restricted to Prevention and Control of Pollution only and shall not be treated as substitute of permission required under other laws of the land.
2. The consent is granted valid for the manufacture of the products / by-products consented quantity as under with capital investment as per schedule II **Rs. 4.95 Crores** Any change / enhancement in production capacity, process, raw materials shall have to be intimated to the board and unit holder has to apply fresh for the same

S.No.	Products / By-product	Maximum Quantity
1	Manufacturing of MS Round, MS Square, Tor Steel, MS Flats, MS Angle Ribbed Bar and TMT Bars.	95880 MT/annum (As per DIC assessment dt: 5-6-2015)

(The unit is registered vide DIC vide No: 07/04/09452 dt: 8-10-2005)

The emissions or discharge of environmental pollutants from the unit / establishment shall not exceed the relevant parameters and standards for the said industry, operation or process specified under respective schedules of the Environment (Protection) Rules, 1986 as amended from time to time.

3. Compliance under Water Act :

a. Effluent standards of discharge of Treated Effluent

Treatment : The unit holder has to operate and maintain a comprehensive effluent treatment system consisting of Primary / Secondary and / or Tertiary treatment so as to achieve the quality of the treated effluent to the following standards of discharge outlet.

Parameters	Conc. in mg/l except for pH
pH	6.0-9.0
Suspended Solids	100
Oil & Grease	10

b. Standards for discharge of Sewerage Treatment

Sewage Treatment – The unit holder has to install a comprehensive treatment system as is warranted with reference to effluent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards before disposal :-

Parameters	Range	Conc. in mg/l except for pH
pH	between	6-9
Suspended Solids	Not to exceed	100
BOD, 3 days, 27°C	Not to exceed	30

c. All the domestic waste water is disposed off through septic tank and soakage pit.

d. Water consumption

- i. The daily quantity of sewage effluent from the unit shall not exceed 02KLD
- ii. The daily quantity of water consumption shall not exceed 15 KLD.

4. Compliance under Air Act:

a. Emission Standards:

Particulate Matter : 250 mg/Nm³

b. The unit holder shall comply to **National Ambient Air Quality Standards** as per EP Act 1986 (refer rule 3(3B)).

