



J&K STATE POLLUTION CONTROL BOARD

Jammu /Srinagar (www.jkspcb.nic.in)

CONSENT ORDER

SPCB --840-- of 2016 dated 13-12-2016

Consent to Establish (Fresh) under section 25/26 of the Water (Prevention & Control of Pollution) Act, 1974, and under section 21 of the Air (Prevention & Control of Pollution) Act, 1981, as amended is granted in favour of

Sh. Samrat Singh

M/s Midway Service Station
Village Karol Ramban

for a period upto November 2017 for a category of Orange as per revised classification of industrial sector, subject to the following terms and conditions in a time bound manner:

1. The consent granted by the Board is restricted to Prevention and Control of Pollution only and shall not be treated as substitute of permission required under other laws of the land.
2. The consent is granted for the establishment of servicing / repairing of the vehicles with capital investment as per schedule I Rs. 20.30 lacs.

S.No.	Products / By-product	Maximum Quantity
1	Automobile Service Station	5-6 Vehicles per day

(The unit is registered vide DIC vide No: 07/022/21/00071 dt: 05-11-2016)

The emissions or discharge of environmental pollutants from the unit / establishment shall not exceed the relevant parameters and standards for the said industry, operation or process specified under respective schedules of the Environment (Protection) Rules, 1986 as amended from time to time.

3. Compliance under Water Act :

a. Effluent standards of discharge of Treated Effluent

Treatment : The unit holder shall install a comprehensive effluent treatment system consisting of Primary / Secondary and / or Tertiary treatment so as to achieve the quality of the treated effluent to the following standards of discharge outlet.

Parameters	Conc. in mg/l except for pH
PH	6.5-8.5
Suspended Solids	100
BOD(3 days at 270 c)Formulation	30
COD	250
Oil & Grease	10

b. Standards for discharge of Sewerage Treatment

Sewage Treatment – The unit holder shall install a comprehensive treatment system as is warranted with reference to effluent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards before disposal :-

Parameters	Range	Conc. in mg/l except for pH
pH	between	6-9
Suspended Solids	Not to exceed	100
BOD, 3 days, 27°C	Not to exceed	30

- c. All the domestic waste water is disposed off through septic tank and soakage pit.

