



J&K STATE POLLUTION CONTROL BOARD
Jammu /Srinagar (www.jkspcb.nic.in)

CONSENT ORDER

SPCB 1328 of 2017 dated 31-3-2017

Consent to **Operate (Renewal)** under section 25/26 of the Water (Prevention & Control of Pollution) Act 1974, and under section 21 of the Air (Prevention & Control of Pollution) Act, 1981, as amended is granted in favour of Sh. Pulkit Aggarwal (Director)

M/s Jai Durga Cement Pvt. Ltd.
Ph I, IGCSamba

for a period upto **March 2019** for **Red** category of unit as per revised classification of industrial sector) subject to the following terms and conditions in a time bound manner :-

1. The consent granted by the Board is restricted to Prevention and Control of Pollution as per Water and Air Act only and shall not be treated as substitute of permission required under other laws of the land.
2. The consent is granted for the manufacturing of the following quantities of products / by-products consented as under with capital investment (as per schedule II) **Rs. 147.95**. Further any change / enhancement in production capacity , process , raw materials shall have be intimated to the board and unit holder has to apply fresh for the same.

S.No.	Products / By-product	Consented quantity
1	Mfg. of PPC Cement	19050 MTPA (As per Sch. II)

(The unit is registered with DIC vide No. 07/04/09618 dt: 18-8-2006)

3. The emissions or discharge of environmental pollutants from the stone crusher shall not exceed the relevant parameters and standards prescribed under respective schedules of the Environment (Protection) Rules , 1986 as amended from time to time.
4. The unit holder shall comply to the **Noise Pollution (Regulation and Control) Rules 2000 as amended** take adequate measures for control of noise from its own sources within the premises so as to maintain ambient air quality standards in respect of noise to less than 75 db(A) during day time and 70 db(A) during night time. Daytime is reckoned in between 6am to 10pm and night time is 10pm to 6am.
5. **Compliance under Water Act:**
Service wastewater (without co processing) : All efforts shall be made by the industry for zero discharge of service wastewater . In case, the industry prefers to discharge service wastewater, the following norms shall be complied with :

Parameters	Conc. in mg/l except for pH
pH	5.5 to 9.0
Suspended Solids	100
Oil & Grease	10
Temperature	Not more than 5 ⁰ C higher than the intake water temperature

- a. The daily quantity of sewage effluent from the unit shall not exceed 3 KLD
- b. The daily quantity of water consumption shall not exceed 05 KLD.
- c. The unit holder shall take adequate safe guards for the treatment of sewerage water by way of providing septic / soakage pit and its discharge shall confirm to the following standards

Parameters	Conc. in mg/l except pH
pH	6 - 9
BOD (3 DAYS 27 ⁰ c)	30
Total Suspended Solid	100

6. **Standards for discharge of Air emissions:**
 - a. The unit holder shall comply to **National Ambient Air Quality Standards** as per EP Act 1986 (refer rule 3(3B) .

