



J&K STATE POLLUTION CONTROL BOARD

Jammu /Srinagar (www.jkspcb.nic.in)

CONSENT ORDER

SPCB 1164 of 2017 dated 03-3-2017

Consent to Operate (Renewal) under section 25/26 of the Water (Prevention & Control of Pollution) Act, 1974, and under section 21 of the Air (Prevention & Control of Pollution) Act, 1981, as amended is granted in favour of Sh. Sudhir Kumar (Managing Director)

M/s K.C Food Products Pvt. Ltd.
Lane 4 SIDCO Industrial Complex Bari Brahamana

for a period upto **January 2022** for **Orange** category of unit as per revised classification of industrial sector, subject to the following terms and conditions in a time bound manner:

- The consent granted by the Board is restricted to Prevention and Control of Pollution only and shall not be treated as substitute of permission required under other laws of the land.
- The consent is granted valid for the manufacture of the products / by-products consented quantity as under with capital investment as per schedule II Rs. **3.56 Crores**. Any change / enhancement in production capacity, process, raw materials shall have to be intimated to the board and unit holder has to apply fresh for the same

S.No.	Products / By-product	Maximum Quantity
1	Manufacturing of different kind of Biscuits	7344 MT/annum

(The unit is registered vide DIC vide No: 07/04/02315/PMT dt: 2-6-1984)

The emissions or discharge of environmental pollutants from the unit / establishment shall not exceed the relevant parameters and standards for the said industry, operation or process specified under respective schedules of the Environment (Protection) Rules, 1986 as amended from time to time.

3. Compliance under Water Act :

a. Standards of discharge for Trade Effluent :

Treatment : The unit holder has to operate and maintain a comprehensive effluent treatment system consisting of Primary / Secondary and / or Tertiary treatment so as to achieve the quality of the treated effluent to the following standards of discharge outlet.

Parameters for (Biscuits production 10 T /day and above)	Conc. in mg/l except for pH
pH	6.5-8.5
BOD(3 days at 27 ^o c)	30
Parameters for (Biscuits production 10 T /day and above)	Disposal via septic tank

b. Standards of discharge for Sewerage disposal:

Sewage Treatment – The applicant has to install a comprehensive treatment system as is warranted with reference to effluent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards before disposal :-

Parameters	Range	Standards of discharge
pH	between	6-9
Suspended Solids	Not to exceed	100 mg/l
BOD, 3 days, 27 ^o C	Not to exceed	30 mg/l

c. All the domestic waste water is disposed off through septic tank and soakage pit. Trade effluent is disposed off through oil and grease trap system.

d. Water consumption

- The daily quantity of sewage effluent from the unit shall not exceed 1.8KLD
- The daily quantity of water consumption shall not exceed 03 KLD.

