



# J&K STATE POLLUTION CONTROL BOARD

Jammu /Srinagar (www.jkspcb.nic.in)

## CONSENT ORDER

SPCB 805 of 2016 dated 28-11-2016

Consent to **Operate (Fresh)** under section 25/26 of the Water (Prevention & Control of Pollution) Act,1974, and under section 21 of the Air (Prevention & Control of Pollution) Act,1981, as amended is granted in favour of

Sh. Vikram Mahajan

M/s ITEC Infra Global Pvt. Ltd.  
Village Rakh Rajpora Bari Brahamana Samba.

for a period upto **One year from date of issue** for a category of **Orange** as per revised classification of industrial sector, subject to the following terms and conditions in a time bound manner:

1. The consent granted by the Board is restricted to Prevention and Control of Pollution only and shall not be treated as substitute of permission required under other laws of the land.
2. The consent is granted valid for the manufacture of the products / by-products consented quantity as under with capital investment as per schedule I **Rs. 51.20 lacs**. Any change / enhancement in production capacity , process , raw materials shall have be intimated to the board and unit holder has to apply fresh for the same

S.No.	Products / By-product	Maximum Quantity
1	Prefabricated Shelters	20 Nos./annum
2	Pre Engineered Building (PEB) / Permanent Bridges	25 Nos./annum
3	Steel Bridges	150 Mtrs./annum
4	Iron Angle Pickets / Observation Tower	125 Mtrs./annum
5	Gate & Grills , Hangers & Doors & windows	200 Mtrs./annum
6	Steel Furniture's	2000 Nos./annum
		(As per Sch II)

(The unit is registered vide DIC vide No: 07/019/11/01222 dt: 13-5-2016)

The emissions or discharge of environmental pollutants from the unit / establishment shall not exceed the relevant parameters and standards for the said industry, operation or process specified under respective schedules of the Environment (Protection) Rules , 1986 as amended from time to time.

### 3. Compliance under Water Act :

#### a. Standards for discharge of sewerage treatment

**Sewage Treatment** – The unit holder has to install a comprehensive treatment system as is warranted with reference to effluent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards before disposal :-

Parameters	Range	Standards of discharge
pH	between	6-9
Suspended Solids	Not to exceed	100 mg/l
BOD, 3 days, 27°C	Not to exceed	30 mg/l

b. All the domestic waste water is disposed off through septic tank and soakage pit.

#### c. Water consumption

- i. The daily quantity of sewage effluent from the unit shall not exceed 0.2 KLD
- ii. The daily quantity of water consumption shall not exceed 0.5 KLD.

### 4. Compliance under Air Act:

- a. The unit holder shall comply to **National Ambient Air Quality Standards** as per EP Act 1986 (refer rule 3(3B) .

