



# J&K STATE POLLUTION CONTROL BOARD

Jammu /Srinagar (www.jkspcb.nic.in)

## CONSENT ORDER

SPCB --- 810 --- of 2016 dated 28-11-2016

Consent to **Operate (Fresh)** under section 25/26 of the Water (Prevention & Control of Pollution) Act, 1974, and under section 21 of the Air (Prevention & Control of Pollution) Act, 1981, as amended is granted in favour of

Sh. Vikram Gupta

M/s Skyline Hotels  
Narwal Bypass Road Jammu

for a period upto **One year from date of issue** for a category of **Orange** as per revised classification of industrial sector, subject to the following terms and conditions in a time bound manner:

1. The consent granted by the Board is restricted to Prevention and Control of Pollution only and shall not be treated as substitute of permission required under other laws of the land.
2. The consent is granted valid for operating the hotel / restaurant facility as under with capital investment as per schedule I Rs. 4549.97 lacs.

S.No.	Hotel / Restaurant Facility	Capacity
1	Rooms	118 Nos.
2	Restaurant	60 seats
3	Bar / Lounge	30 seats
4	Banquet Hall	400 person

The emissions or discharge of environmental pollutants from the hotel shall not exceed the relevant parameters and standards specified under respective schedules of the Environment (Protection) Rules, 1986 as amended from time to time.

### 3. Compliance under Water Act :

#### a. Effluent standards of discharge of treated effluent

**Treatment :** The unit holder has to operate and maintain a comprehensive effluent treatment system consisting of Primary / Secondary and / or Tertiary treatment so as to achieve the quality of the treated effluent to the following standards of discharge outlet.

Parameters	Conc. in mg/l except for pH
PH	5.5 to 9.0
Total Suspended Solids	50
BOD(3 days at 270 c )Formulation	30
Oil & Grease	10
Phosphate as P	1.0

#### b. Standards for discharge of sewerage treatment

**Sewage Treatment** – The applicant has to install a comprehensive treatment system as is warranted with reference to effluent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards before disposal :-

Parameters	Range	Standards of discharge
pH	between	6-9
Suspended Solids	Not to exceed	100 mg/l
BOD, 3 days, 27°C	Not to exceed	30 mg/l

c. All the domestic waste water is disposed off through sewage treatment plant .

#### d. Water consumption

- i. The daily quantity of sewage effluent from the unit shall not exceed 75KLD
- ii. The daily quantity of water consumption shall not exceed 100 KLD.

