



J&K STATE POLLUTION CONTROL BOARD

Jammu / Srinagar (www.jkspcb.nic.in)

CONSENT ORDER

SPCB 485 of 2017 dated 26-7-2017

Consent to Operate (Fresh) under section 25/26 of the Water (Prevention & Control of Pollution) Act, 1974, and under section 21 of the Air (Prevention & Control of Pollution) Act, 1981, as amended is granted in favour of

Mr. Sameer Ahmad Khan

M/s A. K. Motors,
Sheikhpura, Budgam

for a period of one year from the date of issuance of this consent for Orange category of unit as per revised classification of industrial sector, subject to the following terms and conditions in a time bound manner:

1. The consent granted by the Board is restricted to Prevention and Control of Pollution only and shall not be treated as substitute of permission required under other laws of the land.
2. The consent granted is valid for the manufacture of the products / by-products consented quantity as under with capital investment (as per schedule II) Rs. 8.75 lacs. Any change / enhancement in production capacity, process, raw materials shall have be intimated to the board and service station owner has to apply fresh for the same.

S.No.	Products / By-product	Maximum Quantity
1	Wheel Balancing for Medium Vehicles	3000 Nos'/Annum
2	Tyre Repairing	6000 Nos'/Annum
3	Denting, Painting and Repairs Mechanical	1500 Nos/Annum

The emissions or discharge of environmental pollutants from the unit / establishment shall not exceed the relevant parameters and standards for the said industry, operation or process specified under respective schedules of the Environment (Protection) Rules, 1986 as amended from time to time.

3. Compliance under Water Act :

a. Standards of discharge for Trade Effluent :

Treatment – the service station owner has to operate and maintain a comprehensive effluent treatment system consisting of Primary / Secondary and / or Tertiary treatment so as to achieve the quality of the treated effluent to the following standards of discharge outlet:

Parameters	Conc. in mg/l except pH
pH	6.5 – 8.5
Suspended Solids	100
BOD (3 days at 27°C)	30
COD	250
Oil & Grease	10

b. Standards of discharge for Sewerage disposal:

Sewage Treatment – The applicant has to install a comprehensive treatment system as is warranted with reference to effluent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards before disposal :-

Parameters	Range	Conc. in mg/l except pH
pH	Between	6-9
Suspended Solids	Not to exceed	100
BOD, (3 days at 27°C)	Not to exceed	30