



# J&K STATE POLLUTION CONTROL BOARD

Jammu /Srinagar (www.jkspcb.nic.in)

## CONSENT ORDER

SPCB 530 of 2017 dated 16-X-17

Consent to **Operate (Renewal)** under section 25/26 of the Water (Prevention & Control of Pollution) Act, 1974, and under section 21 of the Air (Prevention & Control of Pollution) Act, 1981, as amended is granted in favour of

Mr Abdul Rashid Mugloo

M/s Mughal Darbar Foods,  
Industrial Estate, Khonmoh, Srinagar

for a period up to **May 2018** for a category of **Orange** as per revised classification of industrial sector, subject to the following terms and conditions in a time bound manner:

1. The consent granted by the Board is restricted to Prevention and Control of Pollution only and shall not be treated as substitute of permission required under other laws of the land.
2. The consent is granted valid for the manufacture of the products / by-products consented quantity as under with capital investment as per schedule II **Rs. 96.90 lac. (As per Schedule-II)**. Any change / enhancement in production capacity, process, raw materials shall have be intimated to the board and unit holder has to apply fresh for the same:

S.No.	Products / By-product	Maximum Quantity (As Per Schedule-II/DPR)
1	Canned Vegetables, Cherries, Paneer and Other Fruits	480 Qtls/Annum
2	Wazwn 200 gms	19200 Nos/Annum
3	Wazwan 400 gms	93600 Nos/Annum
4	Canned Wazwan 800 gms	3600 Nos/Annum
5	Canned Wazwan 5000 gms	768 Nos/Annum
6	Pickles	30000 Kgs/Annum
7	Tomato Puree	20000 Kgs/Annum

The emissions or discharge of environmental pollutants from the unit / establishment shall not exceed the relevant parameters and standards for the said industry, operation or process specified under respective schedules of the Environment (Protection) Rules, 1986 as amended from time to time.

### 3. Compliance under Water Act:

#### a. Standard of discharge for Trade Effluent:

**Treatment** – The unit holder has to install, operate and maintain a comprehensive effluent treatment system consisting of Primary / Secondary and / or Tertiary treatment so as to achieve the quality of treated effluent to the following standards:-

	Parameters	Conc. In mg/l except for pH
Above 0.4 MT/day	pH	6.5-8.5
	Suspended Solids	50
	BOD (3 days, 27°C)	30
	Oil & Grease	10
0.1-0.4 Mt/day (10 MT/Yr)	Disposal via septic tank	

#### b. Standards for discharge of sewerage treatment:

**Sewage Treatment** – The unit holder has to install a comprehensive treatment system as is warranted with reference to effluent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards before disposal :-

Parameters	Range	Standards of discharge
pH	between	6-9
Suspended Solids	Not to exceed	100 mg/l
BOD, 3 days, 27°C	Not to exceed	30 mg/l

*Blgs*

